





(Ref. 20116193)

Dry manual cutting of tiles **Usage intensif**



Photo et textes non contractuels

Product Information:

Intensive cutting of ceramic tiles of great thickness.

Locking system by locking and unlocking the separator integrated in the handle: cutting operations are facilitated by one-handed ope ration of locking and unlocking the separator, saving time and incr easing safety.

High rigidity chassis: the aluminum plates are carried on a frame e ntirely in solid aluminum and a central beam in chromed steel. Guides in chromed and ground steels, diameters 20 mm full.

Dual guide system for line-aligned view.

Cutting wheel positioned in front of the separator clearing the view of the path.

Interchangeable cutting wheel with tungsten carbide titanium coat ing.

Large 800 mm support ruler for precise cuts Side supports for large formats

Supplied with:

- 10 mm and 18 mm titanium coated carbide wheels for porcelain

stoneware

- graduated stop
- support rule
- carrying case

Technical characteristics:

Height (cm) : 16.00 Width (cm) : 32.00 Length (cm) : 150.00 Net weight (Kg) : 16.00 Tile width (mm) 1300 Diagonal tile (mm) 920 x 920 Tile thickness (mm) 20 Base dimensions (mm) 1310 x 280 Wheel dimensions Ø x thickness (mm) 10 x 3 and 18 x 3 Breaking power (kg) 1300