



EXPERT 20 PE

(Ref. 20502100)

Dry drilling of metals, plastics and wood (lubrication optional)

Usage régulier

Guarantee:  

Photo et textes non contractuels

Product Information:

- Steel cast iron column
- Transmission by toothed belts and steel pulleys
- Spindle mounted on ball bearings
- On/off switch equipped with undervoltage coil
- Punch-to-Hook Stop
- Servo chuck protection shield
- Square table tiltable up to 45°, with cutting fluid recuperator
- Moving the table by rack
- Digital display for drilling depth
- Digital display of spindle speed Laser drilling position
- LED lighting
- Pulley cover equipped with a claw safety microswitch

Accessories delivered as standard:

- 16 mm self-tightening chuck
- Chuck shank
- Cone flush
- Screw vice and set of flanges

Technical characteristics:

- Height (cm) : 98.00
- Width (cm) : 43.00
- Length (cm) : 66.00
- Net weight (Kg) : 49.00
- Power(kW) 0.55
- Power (V) 1-phase 230V
- Spindle speed (rpm) 210 - 2880
- Max. drilling capacity (mm) 20
- Morse taper MT2
- Column dia (mm) 72
- Spindle stroke (mm) 85
- Number of gears 16
- d: spindle/column distance (mm) 160
- e: spindle/base distance (mm) 630
- f: spindle/table distance (mm) 440
- Table dimension (mm) 286 x 286
- Lighting Yes
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No