



EXPERT 22 PE TRI

(Ref. 20502102)

Dry drilling of metals, plastic materials and wood (lubrification en option)

Usage régulier

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron column Transmission through steel dented belt and wheels Spindle fitted on bearings ON/OFF switch fitted with a lack of voltage coil Emergency Stop through mushroom stay put button Protective shield of servo chuck Tilting square table up to 45°, with liquid collector Rack-driven table Digital readout of the drilling depth Digital display of the spindle speed Drilling-position laser LED lighting Pulley cover fitted with a grip-safety microswitch

Accessoires livrés de série :

- Mandrin auto-serrant 16 mm
- Queue de mandrin
- Chasse cône
- Etau à vis et jeu de brides

Technical characteristics:

Height (cm) : 98.00
Width (cm) : 43.00
Length (cm) : 66.00
Net weight (Kg) : 60.00
Power(kW) 0.75
Power (V) 3-phase 400V
Spindle speed (rpm) 210 - 2880
Max. drilling capacity (mm) 22
Morse taper MT2
Column dia (mm) 72
Spindle stroke (mm) 85
Number of gears 16
d: spindle/column distance (mm) 180
e: spindle/base distance (mm) 600
f: spindle/table distance (mm) 415
Table dimension (mm) 305 x 305
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No