



## 363 S

(Ref. 20105052)

Sanding of metals, wood, plastics

**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

brush made of brassed steel wires Ø 250 mm, thickness 35 mm, bore hole 32 mm  
Transmission through anti-slipping rubber roller  
Graphite-coated canvas ensuring a good running of the band  
Lack of tension-coil switch  
Thermal circuit breaker  
2-gear motor  
Emergency Stop through mushroom stay put button  
24V very low voltage control  
Reinforced metal sheet protective cover fitted with dust collection nozzle Ø 100 mm  
R0° to 90° orientable band cover for horizontal or vertical job, and band end job  
Hot weather adaptation on request  
Can be modified to 230V three-phase on request  
Supplied fitted on stand  
Optional suction system (20105053)

### Technical characteristics:

Height (cm) : 122.00  
Width (cm) : 70.00  
Length (cm) : 83.00  
Net weight (Kg) : 100.00  
Power(kW) 1.27 / 1.7  
Power (V) 3-phase 400V  
Rotation speed (rpm) 1400 / 2800  
Endless band dimension (mm) 1500 x 120  
Working surface table (mm) 445 x 120  
Band speed (m/s) 15 / 30  
Integrated dust suction optional

### Supplied with his Stand