



JET 15

(Ref. 20402004)

Usage très intensif

Norm: EN 60335-2-69

Garantie:  

Photo et textes non contractuels

Product Information:

"Fitted with a high-efficiency 99.9% Class M filter
Metal accessories and stainless steel tubes
Anti-crushing shielded hose
4-wheel stand for optimised motion
Dual-turbine suction
By-pass cooling down system motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
Anti-static electricity plate connected to earth
Neoprene power table HO7 RNF length 7 m

"Standard metal accessories:

- Straight tubes 2 x 500 mm + 1 bent tube
 - 1 liquid nozzle - 400 mm
 - 1 dual-purpose nozzle - 270 mm
- Standard plastic accessories:
- 1 round brush
 - 1 flat nozzle
 - 1 Padding nozzle
 - 1 hose - 2200 mm

Technical characteristics:

Height (cm) : 54.00
Width (cm) : 35.00
Length (cm) : 35.00
Net weight (Kg) : 9.89
Power (W) 1000
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l) 10
Depression (Kpa) 21.56
Flow (l/min) 3 500
Sound level (dBA) 75
Atex Zone 22 No
Accessory diameter (mm) 32
Unclogging No
Class-M approved No
Vacuum cleaner filter Class M
Synchro socket No
Cable length (m) 7
Tank capacity (L) 17