



Photo et textes non contractuels

## JET 30 i

(Ref. 20402041)

Water and dust suction  
**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  

### Product Information:

"Manual unclogging system of the filter using a single button  
Water-resistant high-efficiency 9.9% Class M cartridge filter  
Metal accessories and stainless steel tubes  
Carbon-fibre reinforced base  
Storage unit of accessories integrated to the base  
Large reinforced 2-wheel + 2-caster base for an optimised stability  
Anti-crushing shielded hose  
By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
Suction, depression and cutting-off high-performance Anti-static electricity plate connected to earth  
Neoprene power table HO7 RNF length 7 m"

#### Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 2.5 m
- Dust nozzle - 400 mm
- liquid nozzle - 400 mm
- round brush
- flat nozzle
- round brush fitting
- Class M cartridge filter PTFE

### Technical characteristics:

Height (cm) : 80.00  
Width (cm) : 54.00  
Length (cm) : 45.00  
Net weight (Kg) : 16.60  
Power (W) 1450  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l) 35  
Depression (Kpa) 26.7  
Flow (l/min) 4200  
Sound level (dBA) 74  
Atex Zone 22 No  
Accessory diameter (mm) 40  
Unclogging Yes  
Class-M approved No  
Vacuum cleaner filter Class M PET cartridge  
Synchro socket No  
Cable length (m) 7  
Tank capacity (L) 38