



STAR 16 PE

(Ref. 20501017)

Dry drilling of metals, plastic materials and wood
Usage d'appoint

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron column
V-belt transmission
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Safety-grip microswitch around belt cover
Protective shield of servo chuck
Tilting table up to 45 °
Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 54.00
Width (cm) : 31.00
Length (cm) : 85.00
Net weight (Kg) : 32.60
Power(kW) 0.4
Power (V) 1-phase 230V
Spindle speed (rpm) 200 - 2500
Max. drilling capacity (mm) 16
Morse taper MT2
Column dia (mm) 60
Spindle stroke (mm) 60
Number of gears 12
d: spindle/column distance (mm) 125
e: spindle/base distance (mm) 535
f: spindle/table distance (mm) 420
Table dimension (mm) 200 x 200
Distance between table grooves (mm) 112
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No