



## 30 CV

(Ref. 20502022)

Drilling and tapping of metals, plastic materials and wood, with coolant

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Spindle fitted on bearings  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Locking main switch 4 points  
Semi automatic tapping system + instant return  
Servo detachable chuck protective shield  
Large table mécanicien, Rack-driven table  
Electronic speed variator  
Digital display of the spindle speed  
LED lighting 24 V

#### Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

### Technical characteristics:

Height (cm) : 176.50  
Width (cm) : 52.50  
Length (cm) : 66.00  
Net weight (Kg) : 220.00  
Power(kW) 1.5  
Power (V) 3-phase 400V  
Spindle speed (rpm) 150 : 3000  
Max. drilling capacity (mm) 30  
Max. tapping capacity (mm) M16  
Morse taper MT3  
Column dia (mm) 92  
Spindle stroke (mm) 135  
Number of gears Variable  
d: spindle/column distance (mm) 204  
e: spindle/base distance (mm) 1 150  
f: spindle/table distance (mm) 185-605  
Table dimension (mm) 460 x 360  
Distance between table grooves (mm) 135  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping Yes  
Cross motion table No