



## 40 CV

(Ref. 20502023)

Drilling and tapping of metals, plastic materials and wood, with coolant

**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Spindle fitted on bearings  
High efficiency class IE2 motor  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Locking main switch 4 points  
Semi automatic tapping system + instant return  
Servo detachable chuck protective shield  
Large table mécanicien, Rack-driven table  
Electronic speed variator  
Digital display of the spindle speed  
LED lighting 24 V

### Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

### Technical characteristics:

Height (cm) : 193.00  
Width (cm) : 56.00  
Length (cm) : 89.00  
Net weight (Kg) : 320.00  
Power(kW) 1.5  
Power (V) 3-phase 400V  
Spindle speed (rpm) 65 : 2000  
Max. drilling capacity (mm) 40  
Max. tapping capacity (mm) M20  
Morse taper MT4  
Column dia (mm) 115  
Spindle stroke (mm) 150  
Number of gears Variable  
d: spindle/column distance (mm) 265  
e: spindle/base distance (mm) 1 040  
f: spindle/table distance (mm) 140-860  
Table dimension (mm) 560 x 475  
Distance between table grooves (mm) 220  
Lighting Yes  
Servo screen Yes  
Reversible vice table No  
Coolant Yes  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping Yes  
Cross motion table No