



Photo et textes non contractuels

## 35 CTE

(Ref. 20502029)

Drilling and tapping of metals, plastic materials and wood, with coolant

**Usage intensif**

Guarantee:  

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
V-belt transmission with tension adjustment  
Spindle fitted on bearings  
Adjustable spindle rack motion through return spring  
Drilling-depth stop  
2-gear motor  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Safety microswitch of the pulley cover  
Système de Semi automatique tapping avec inversion manuelle, Capacity M16  
Servo polycarbonate screen  
LED lighting 24 V  
2-position reversible vice table, vernier  
Vice fitted on guideways  
Rack-driven table

#### Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 180.00  
Width (cm) : 55.00  
Length (cm) : 84.00  
Net weight (Kg) : 270.00  
Power(kW) 1.5  
Power (V) 3-phase 400V  
Spindle speed (rpm) 115 - 1910  
Max. drilling capacity (mm) 35  
Max. tapping capacity (mm) 16  
Morse taper MT4  
Column dia (mm) 102  
Spindle stroke (mm) 140  
Number of gears 18  
d: spindle/column distance (mm) 230  
e: spindle/base distance (mm) 1 230  
f: spindle/table distance (mm) 100-680  
Table dimension (mm) 380 x 380  
Distance between table grooves (mm) 2 x 77  
Lighting Yes  
Servo screen Yes  
Reversible vice table Yes  
Coolant Yes  
Jaw width (mm) 120  
Jaw height (mm) 40  
Opening (mm) 120  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping Yes  
Cross motion table No