



## 75 PM B

(Ref. 20502048)

Drilling, drill-coring and tapping steel with coolant  
**Usage intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Robust and versatile magnetic drilling machine  
4 gears through gears  
Inversion of rotational direction to tap M3 to M14  
MT3 Spindle  
Protective shield  
Left/Right 15° side rotation base  
Forward/Backwards motion base (20 mm)  
Built-in coolant tank  
Coolant through tool center

#### Supplied with:

- Mill-holder shaft Weldon 19 mm
- Chuck fitting
- Wrench chuck 16 mm for drill
- Transport case
- Safety chain
- Outils

### Technical characteristics:

Height (cm) : 58.00  
Width (cm) : 28.00  
Length (cm) : 40.00  
Net weight (Kg) : 27.80  
Power(kW) 1.8  
Power (V) 1-phase 230V  
Load speed (rpm) 90 / 120 / 180 / 230  
Mill (D x Length maxi) 12 à 75 x 50  
Drill 32 x 150  
Taps M3 à M25 x 40  
Spindle stroke (mm) 145  
Magnetic force (N) 32 000  
Basic dimension (mm) 200 x 100  
Box of mills No  
Mill Max. machining Ø 75  
Drill Max. machining Ø 32  
Tap Max. machining Ø M25