



SPC 40 TC DL

(Ref. 20601138)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

Cross move table, Slow down motion
Steel cast iron frame, head and stand
Steel column
Machined aluminium pulleys
Transmission through V belts with rapid adjustment of tension
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
2-gear motor
24V very low voltage controls :
- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stop button
- 3-point locking circuit breaker
Detachable servo protective shield
24V lighting
Electrical protection IP54
Noise level 50 dB
Rack-driven table, graisseur de la vis sans fin
Hot weather adaptation on request
Can be modified to 230V three-phase on request
Machined aluminium pulleys

Supplied with Self-clamping chuck and Chuck shank

Technical characteristics:

Height (cm) : 185.00
Width (cm) : 47.50
Length (cm) : 90.00
Net weight (Kg) : 570.00
Power(kW) 0.8 / 1.47
Power (V) 3-phase 400V
Spindle speed (rpm) 45-1650
Max. drilling capacity (mm) 40
Milling capacity (mm) 80
Morse taper MT4
Column dia (mm) 140
Spindle stroke (mm) 150
Number of gears 14
d: spindle/column distance (mm) 300
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm) 50-610
Table dimension (mm) 300 x 540
Distance between table grooves (mm) 150
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Transversal / longitudinal stroke (mm) 300 x 410
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping No
Cross motion table Yes