



Photo et textes non contractuels

Product Information:

Cast aluminium body
Fitted with self-lubricated oiltight bearings
Electrical brake powered by an Emergency Stop, stop in less than 5 seconds
Control box complying with high school and administration requirements
24V very low voltage controls
Start/Stop switch
Switching on lamp
3-point locking circuit breaker
Lack of voltage-coil safety device
Polycarbonate protective shield
Motor internal automatic heat protection
Pressed metal sheet carters fitted with a nozzle to collect dust
Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
Hot weather adaptation on request
3-phase 230V version of the bench grinder on request

Supplied with:

- Grinding Wheel A 60 M
- Brass Wire Brush

ULTRA 200 TBT FR

(Ref. 20113136)

Dry grinding and polishing of ferrous metals
Usage très intensif

Guarantee:  **3** 

Technical characteristics:

Height (cm) : 55.00
Width (cm) : 33.00
Length (cm) : 60.00
Net weight (Kg) : 29.00
Power(kW)
Power (V) 3-phase 400V
Rotation speed 1 (rpm)
Wheel-1 dimension (mm)
Brush dimensions (mm)
Wheel-1 grain
Brush wire nature Brass-coated steel
Diameter (mm)