



SR 374 DG DAV

(Ref. 20114102)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage intensif

Guarantee:  3 

Photo et textes non contractuels

Product Information:

"Electronic speed variator
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Rapid clamping vice monté sur glissière à rattrapage de jeu
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor
Oil cylinder controlling the down move of the arch through a gravity-feed system"

Technical characteristics:

Height (cm) : 155.00
Width (cm) : 96.00
Length (cm) : 178.00
Net weight (Kg) : 595.00
Power(kW)
Power (V) 3-phase 400V
Speed (m/min)
Round cutting capacity (mm) at 90°
Square cutting capacity (mm) at 90°
Rectangle cutting capacity (mm) at 90°
Left round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°
Left rectangle cutting capacity (mm) at 45°
Left round cutting capacity (mm) at 60°
Left square cutting capacity (mm) at 60°
Left rectangle cutting capacity (mm) at 60°
Vice opening (mm)
Working height (mm)
Tape (mm)
Right rectangle cutting capacity (mm) at 45°
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°