



Photo et textes non contractuels

## Product Information:

Left and right cutting  
Autonomous down move of the arch  
Very highly rigid steel cast iron arch  
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band  
Adjustable front mobile band guide  
2-point lubrication system through electropump  
Vice support tilting with the arch  
Hydraulic vice  
24V very low voltage controls  
Emergency Stop through mushroom stay put button  
Band cover fitted with a microswitch  
Motor protection through thermal circuit breaker  
Electrical protection IP54  
Coaxial reducer motor

## Supplie with:

- base
- band saw
- adjustable cut stop

## SR 264 DG DA

(Ref. 20114122)

### Usage intensif

Guarantee:  CE

## Technical characteristics:

Height (cm) : 140.00  
Width (cm) : 66.00  
Length (cm) : 140.00  
Net weight (Kg) : 302.00  
Power(kW)  
Power (V) 3-phases 400V  
Speed (m/min)  
Round cutting capacity (mm) at 90°  
Squre cutting capacity (mm) at 90°  
Rectangle cutting capacity (mm) at 90°  
Left round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°  
Left rectangle cutting capacity (mm) at 45°  
Left round cutting capacity (mm) at 60°  
Left square cutting capacity (mm) at 60°  
Left rectangle cutting capacity (mm) at 60°  
Vice opening (mm)  
Working height (mm)  
Tape (mm)  
Right rectangle cutting capacity (mm) at 45°  
Right round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°