



Photo et textes non contractuels

## Product Information:

Cuts left and right  
Aircast fram  
Saw blade guides equipped with bearings and carbide pads to ensure excellent resistance to saw blade wear  
Adjustable anterior tape guide  
Autonomous descent by gravity controlled by hydraulic cylinder  
2-point electro-pump lubrication device  
Safety micro-switch and tension gauge saw blade  
Fast-tightening set mounted on game catch-up slide  
Control desk in front  
Very low voltage controls 24 V  
Stopping punch to hook  
Carter saw equipped with a positive micro-reuptor  
Motor protection by heat breaker  
Motor with coaxial gearbox

**Supplied with base, saw blade and 500 mm adjustable cut stop**

## EXPERT 250 SR DGDA

(Ref. 20114136)

Dry steel sawing with coolant  
**Usage régulier**

Guarantee: **CE**

## Technical characteristics:

Height (cm) : 180.00  
Width (cm) : 100.00  
Length (cm) : 185.00  
Net weight (Kg) : 306.00  
Power(kW)  
Power (V) 3-phase 400V  
Speed (m/min)  
Round cutting capacity (mm) at 90°  
Squre cutting capacity (mm) at 90°  
Rectangle cutting capacity (mm) at 90°  
Left round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°  
Left rectangle cutting capacity (mm) at 45°  
Left round cutting capacity (mm) at 60°  
Left square cutting capacity (mm) at 60°  
Left rectangle cutting capacity (mm) at 60°  
Vice opening (mm)  
Working height (mm)  
Tape (mm)  
Right rectangle cutting capacity (mm) at 45°  
Right round cutting capacity (mm) at 45°  
Left square cutting capacity (mm) at 45°