



Photo et textes non contractuels

## EXPERT 250 SR DAV TRI

(Ref. 20114138)

Dry steel, stainless steel and aluminium sawing with coolant  
**Usage régulier**

Guarantee:  

### Product Information:

- Steel cast iron arch
- Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
- Adjustable front mobile band guide
- Gravity-feed separate down move through oil cylinder
- 2-point lubrication system through electropump
- Band-tension microswitch and pressure gauge
- Rapid clamping vice monté sur glissière à rattrapage de jeu
- Band speed variator
- Front control panel
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a positive microswitch
- Motor protection through thermal circuit breaker
- Coaxial reducer motor

### Technical characteristics:

- Height (cm) : 173.00
- Width (cm) : 54.00
- Length (cm) : 180.00
- Net weight (Kg) : 212.00
- Power(kW)
- Power (V) 3-phase 400V
- Speed (m/min)
- Round cutting capacity (mm) at 90°
- Square cutting capacity (mm) at 90°
- Rectangle cutting capacity (mm) at 90°
- Left round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°
- Left rectangle cutting capacity (mm) at 45°
- Left round cutting capacity (mm) at 60°
- Left square cutting capacity (mm) at 60°
- Left rectangle cutting capacity (mm) at 60°
- Vice opening (mm)
- Working height (mm)
- Tape (mm)

Supplied with base, saw blade and 500 mm adjustable cut stop