

steel tank



Photo et textes non contractuels

JET 30 i DR

(Ref. 20402052)

Water, dust, soot and ash aspiration

Usage très intensif

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Manual unclogging system of the filter using a single button
special class M cartridge filter for fuel soot
Anti-clogging nylon over filter
Metal accessories and stainless steel tubes
Carbon-fibre reinforced base
Storage unit of accessories integrated to the base
Large reinforced 2-wheel + 2-castor base for an optimised stability
Anti-crushing shielded hose
By-pass cooling down system 1450W motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)
Suction, depression and cutting-off high-performance
Anti-static electricity plate connected to earth
Neoprene power table HO7 RNF length 7 m"

Standard accessories:

- Bent tubes 2 x 500 mm Ø 40 mm
- hose Ø 40 mm, length 5 m
- Dust nozzle - 400 mm
- flat nozzle inox 600 mm
- Class H cartridge filter PTFE

Technical characteristics:

Height (cm) : 83.00
Width (cm) : 54.00
Length (cm) : 45.00
Net weight (Kg) : 16.40
Power (W)
Power (V) 1-phase 230V
Tank stainless steel
Tank capacity (l)
Depression (Kpa) 26.7
Flow (l/min) 4 200
Sound level (dBA)
Atex Zone 22 No
Accessory diameter (mm)
Unclogging Yes
Class-M approved No
Vacuum cleaner filter Class H cartridge
Synchro socket No
Cable length (m)
Tank capacity (L)