



Photo et textes non contractuels

MC 30 i

(Ref. 20403005)

Water and dust suction

Usage régulier

Norm: EN 60335-2-69

Guarantee:  

Product Information:

"Fitted with a class L filter

Anti-crushing shielded hose

4-wheel stand for optimised motion

Dual turbine suction

By-pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down). Designed for heavy-duty jobs

Vinyl power cable H05 VV-F length 7 m

Standard accessories:

- telescopic steel tube Ø 32 mm
- dual-purpose dust nozzle
- liquid nozzle
- round brush
- flat nozzle
- padding nozzle
- hose, length 2,6 m Ø 32 mm

Technical characteristics:

Height (cm) : 41.00

Width (cm) : 41.00

Length (cm) : 75.00

Net weight (Kg) : 12.00

Repairability index

Power (W)

Power (V) 1-phase 230V

Tank stainless steel

Tank capacity (l)

Depression (Kpa) 22.54

Flow (l/min) 3 530

Sound level (dBA) 69.5

Atex Zone 22 No

Accessory diameter (mm)

Unclogging No

Class-M approved No

Vacuum cleaner filter Class L

Synchro socket No

Cable length (m)

Tank capacity (L)