



STAR 26 PC

(Ref. 20501020)

Dry drilling of metals, plastic materials and wood
Usage d'appoint

Guarantee:  

Photo et textes non contractuels

Product Information:

Steel cast iron column
V-belt transmission
Spindle fitted on bearings
ON/OFF switch fitted with a lack of voltage coil
Emergency Stop through mushroom stay put button
Safety-grip microswitch around belt cover
Protective shield of servo chuck
Tilting table up to 45 °
Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 162.50
Width (cm) : 36.00
Length (cm) : 68.00
Net weight (Kg) : 78.00
Power(kW)
Power (V) 1-phase 230V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm)
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Jaw width (mm)
Jaw height (mm)
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No