



SPC 40 TC VEL DL T

(Ref. 20601147)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee:  **3** 

Photo et textes non contractuels

Product Information:

- Semi automatic tapping
- Cross move table
- Electronic speed variator
- Slow down motion
- Steel cast iron frame, head and stand
- Steel column
- Machined aluminium pulleys
- Transmission through V belts with rapid adjustment of tension
- Spindle fitted on bearings
- Adjustable spindle rack motion through return spring
- 24V very low voltage controls :
 - ON/OFF
 - Switching on lamp
 - Emergency Stop through mushroom stay put button
 - 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- Rack-driven table, graisseur de la vis sans fin

Technical characteristics:

- Height (cm) : 185.00
- Width (cm) : 47.50
- Length (cm) : 90.00
- Net weight (Kg) : 410.00
- Power(kW)
- Power (V) 3-phase 400V
- Spindle speed (rpm)
- Max. drilling capacity (mm)
- Milling capacity (mm)
- Morse taper MT4
- Column dia (mm)
- Spindle stroke (mm)
- Number of gears
- d: spindle/column distance (mm)
- e: spindle/base distance (mm) 1 150
- f: spindle/table distance (mm)
- Table dimension (mm)
- Distance between table grooves (mm)
- Lighting Yes
- Servo screen Yes

Hot weather adaptation on request
Can be modified to 230V three-phase on request
Machined aluminium pulleys

Transversal / longitudinal stroke (mm)
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping Yes
Cross motion table Yes

Supplied with Self-clamping chuck and Chuck shank