

121

(Ref. 20113010)

Dry grinding and polishing of ferrous metals
Usage très intensif

Guarantee: 3 ans

Photo et textes non contractuels

Product Information:

"Cast aluminium body
Fitted with self-lubricated oiltight bearings
Control box complying with high school and administration requirements
4-point locking Start/Stop switch
Lack of voltage-coil safety device
Emergency Stop with mushroom stay put button
Polycarbonate protective shield
Motor internal automatic heat protection
Pressed metal sheet carters fitted with a nozzle to collect dust
Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
Hot weather adaptation on request
3-phase 230V version of the bench grinder on request

Supplied with:
- Grinding Wheel A 60 M
- Brass Wire Brush

Technical characteristics:

Height (cm) : 37.00
Width (cm) : 24.00
Length (cm) : 53.00
Net weight (Kg) : 15.80
Power(kW)
Power (V) 3-phase 400V
Rotation speed 1 (rpm) 2 800
Wheel-1 dimension (mm)
Brush dimensions (mm)
Wheel-1 grain
Brush wire nature Brass coated steel
Diameter (mm)

SIDAMO - ZI des Gailletrous - 41260 La Chaussée St Victor
Tél : +33 (0)2 54 90 28 28 - Fax : 08 97 65 65 10 - Mail : sidamo@sidamo.com - Service utilisateur / Tél : 02 54 74 02 16