



SR 260 BSA

(Ref. 20114035)

Dry steel sawing with coolant
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Fully-hydraulic semi automatic cycle of band, arch and arch
- Very highly rigid cast aluminium arch
- 3-point lubrication system through electropump
- Detachable vice support
- Band tension microswitch through rotation detection
- Adjustable band tension through automatic stop safety system in case the band breaks or slips
- Adjustable band guides fitted with carbide tips and bearings
- Easy rotation of arch with bearings (45° to the right and 60° to the left)
- Feed and cutting pressure adjustment system
- 24V very low voltage controls
- Motor protection through thermal circuit breaker
- Electrical protection IP54
- Locking main switch
- Emergency Stop through mushroom stay put button
- Band cover fitted with a positive microswitch
- Hydraulic vice
- Bac liquide de refroidissement de 40 litres de contenance
- Hot weather adaptation on request
- Can be modified to 230V three-phase on request

Technical characteristics:

- Height (cm) : 130.00
- Width (cm) : 120.00
- Length (cm) : 70.00
- Net weight (Kg) : 320.00
- Power(kW)
- Power (V) 3-phase 400V
- Speed (m/min)
- Round cutting capacity (mm) at 90°
- Square cutting capacity (mm) at 90°
- Rectangle cutting capacity (mm) at 90°
- Left round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°

Supplied with stand, band and cutting stop 600 mm