



## SR 170 MV

(Ref. 20114099)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Cast aluminium arch
- Tilting arch for left cuts up to 60°
- Band guides fitted with bearings
- Adjustable front mobile band guide
- Arch return spring
- Two-point lubrication system using an electro pump
- Manual adjustment of band tension
- Rapid clamping vice
- Coaxial reducer motor
- Electronic speed variator
- Adjustable trigger switch handle
- Emergency Stop with mushroom stay put button

Supplied with Stand, ruban, and butée de coupe

### Technical characteristics:

- Height (cm) : 160.00
- Width (cm) : 100.00
- Length (cm) : 51.00
- Net weight (Kg) : 102.00
- Power(kW)
- Power (V) 1-phase 230V
- Speed (m/min) 20 : 65
- Round cutting capacity (mm) at 90°
- Square cutting capacity (mm) at 90°
- Rectangle cutting capacity (mm) at 90°
- Left round cutting capacity (mm) at 45°
- Left square cutting capacity (mm) at 45°
- Left rectangle cutting capacity (mm) at 45°
- Left round cutting capacity (mm) at 60°
- Left square cutting capacity (mm) at 60°
- Left rectangle cutting capacity (mm) at 60°
- Vice opening (mm)
- Working height (mm)
- Tape (mm)