



## JET 60

(Ref. 20402005)

**Usage très intensif**

Norm: EN 60335-2-69

Guarantee:  3 €

**Photo et textes non contractuels**

### Product Information:

"Fitted with a high-efficiency 99.9% Class M filter  
Metal accessories and stainless steel tubes  
Anti-crushing shielded hose  
Tilting tank to easily empty liquids  
Trolley fitted with 4 wheels for an optimised motion  
Dual turbine suction  
By-pass cooling down system motor designed for continuous heavy-duty jobs (air is sucked by a third turbine on top of the motor, only for cooling down)  
Anti-static electricity plate connected to earth  
Neoprene power cable HO7 RNF length 7 m

#### "Standard metal accessories:

- 2 user-friendly bent tubes ensuring a quiet use
- 1 Dust nozzle - 400 mm
- 1 liquid nozzle - 400 mm
- 1 accessory support

#### Standard plastic accessories:

- 1 round brush
- 1 flat nozzle
- 1 round brush fitting
- 1 hose - 2500 mm

### Technical characteristics:

Height (cm) : 90.00  
Width (cm) : 56.00  
Length (cm) : 60.00  
Net weight (Kg) : 30.00  
Power (W)  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l)  
Depression (Kpa) 23.52  
Flow (l/min) 7 070  
Sound level (dBA) 84.4  
Atex Zone 22 No  
Accessory diameter (mm)  
Unclogging No  
Class-M approved No  
Vacuum cleaner filter Class M  
Synchro socket No  
Cable length (m)  
Tank capacity (L)