



Photo et textes non contractuels

40 CV

(Ref. 20502023)

Drilling and tapping of metals, plastic materials and wood, with coolant

Usage intensif

Guarantee:  

Product Information:

Steel cast iron frame, head and stand
Steel column
Spindle fitted on bearings
High efficiency class IE2 motor
24V very low voltage controls
Emergency Stop through mushroom stay put button
Locking main switch 4 points
Semi automatic tapping system + instant return
Servo detachable chuck protective shield
Large table mécanicien, Rack-driven table
Electronic speed variator
Digital display of the spindle speed
LED lighting 24 V

Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- BSH 7 vice and set of clamps

Technical characteristics:

Height (cm) : 193.00
Width (cm) : 56.00
Length (cm) : 89.00
Net weight (Kg) : 320.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Max. tapping capacity (mm)
Morse taper MT4
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 040
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping Yes
Cross motion table No