



Photo et textes non contractuels

30 CTE IE3

(Ref. 20502063)

Drilling metals, plastic materials and wood, with coolant
Usage intensif

Guarantee:  

Product Information:

Steel cast iron frame, head and stand
Steel column
V-belt transmission with tension adjustment
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
Drilling-depth stop
High-efficiency IE3 motor
Controls
Emergency Stop through mushroom stop button
Safety microswitch of the pulley cover
Servo polycarbonate screen
LED lighting 24 V
2-position reversible vice table, vernier
Vice fitted on guideways
Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank

Technical characteristics:

Height (cm) : 200.00
Width (cm) : 60.00
Length (cm) : 89.00
Net weight (Kg) : 255.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 275
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant Yes
Jaw width (mm)
Jaw height (mm)
Opening (mm)
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No