



30 CTE IE3

(Ref. 20502063)

Drilling metals, plastic materials and wood, with coolant
Usage intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Steel cast iron frame, head and stand
- Steel column
- V-belt transmission with tension adjustment
- Spindle fitted on bearings
- Adjustable spindle rack motion through return spring
- Drilling-depth stop
- High-efficiency IE3 motor
- Controls
- Emergency Stop through mushroom stay put button
- Safety microswitch of the pulley cover
- Servo polycarbonate screen
- LED lighting 24 V
- 2-position reversible vice table, vernier
- Vice fitted on guideways
- Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank

Technical characteristics:

- Height (cm) : 200.00
- Width (cm) : 60.00
- Length (cm) : 89.00
- Net weight (Kg) : 255.00
- Power(kW)
- Power (V) 3-phase 400V
- Spindle speed (rpm)
- Max. drilling capacity (mm)
- Morse taper MT3
- Column dia (mm)
- Spindle stroke (mm)
- Number of gears
- d: spindle/column distance (mm)
- e: spindle/base distance (mm) 1 275
- f: spindle/table distance (mm)
- Table dimension (mm)
- Distance between table grooves (mm)
- Lighting Yes
- Servo screen Yes
- Reversible vice table Yes
- Coolant Yes
- Jaw width (mm)
- Jaw height (mm)
- Opening (mm)
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No