



Photo et textes non contractuels

30 CVTE

(Ref. 20502066)

Drilling and tapping of metals, plastic materials and wood, with coolant

Usage intensif

Guarantee:  

Product Information:

Steel cast iron frame, head and stand
Steel column
Transmission through Poly V belts with tension adjustment
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
Drilling-depth stop
Electronic speed variator
Digital display of the spindle speed
Controls : Emergency Stop through mushroom stop button, Safety microswitch of the pulley cover, Spindle speed override button
Servo detachable chuck protective shield
LED lighting 12 V - 6 W
2-position reversible vice table, vernier
Vice fitted on guideways
Rack-driven table

Supplied with:

-Self-clamping chuck,
-Chuck shank,
-Taper drift

Technical characteristics:

Height (cm) : 175.00
Width (cm) : 77.00
Length (cm) : 65.00
Net weight (Kg) : 187.90
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table Yes
Coolant Yes
Jaw width (mm)
Jaw height (mm)
Opening (mm)
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No