



Photo et textes non contractuels

PRO 32 PC

(Ref. 20502089)

Drilling metals, plastic materials and wood
Usage intensif

Guarantee:  

Product Information:

Steel cast iron frame, head and stand
V-belt transmission with tension adjustment
Spindle fitted on bearings
Adjustable spindle mack motion through return spring
Drilling-depth stop
Steel column
Very low voltage controls 24 V
Emergency Stop through mushroom stay put button
Safety microswitch of the pulley cover
Servo polycarbonate screen
Rack-driven table

Supplied with:

- Key less chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

Height (cm) : 176.00
Width (cm) : 56.00
Length (cm) : 85.00
Net weight (Kg) : 205.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Morse taper MT3
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm)
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting No
Servo screen Yes
Reversible vice table No
Coolant No
Jaw width (mm)
Jaw height (mm)
Opening (mm)
Automatic down motion (mm/tr) No
Slow down motion No
Semi automatic tapping No
Cross motion table No