



Photo et textes non contractuels

## SPC 32 TE VEL T

(Ref. 20601125)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  

### Product Information:

Steel cast iron frame, head and stand  
Steel column  
Machined aluminium pulleys  
Transmission through V belts with rapid adjustment of tension  
Spindle fitted on bearings  
Adjustable spindle rack motion through return spring  
24V very low voltage controls  
ON/OFF  
Switching on lamp  
Emergency Stop through mushroom stop button

3-point locking circuit breaker  
Detachable servo protective shield  
24V lighting  
Semi automatic tapping  
Electronic speed variator  
Electrical protection IP54  
Noise level 50 dB  
3-position reversible vice table (with vernier), V jaws to drill tubes  
Vice fitted on guideways to center the part to drill  
Rack-driven table, graisseur de la vis sans fin  
Hot weather adaptation on request  
Can be modified to 230V three-phase on request

### Technical characteristics:

Height (cm) : 180.00  
Width (cm) : 43.50  
Length (cm) : 88.00  
Net weight (Kg) : 300.00  
Power(kW)  
Power (V) 3-phase 400V  
Spindle speed (rpm)  
Max. drilling capacity (mm)  
Morse taper MT3  
Column dia (mm)  
Spindle stroke (mm)  
Number of gears  
d: spindle/column distance (mm)  
e: spindle/base distance (mm) 1 210  
f: spindle/table distance (mm)  
Table dimension (mm)  
Distance between table grooves (mm)  
Lighting Yes  
Servo screen Yes  
Reversible vice table Yes  
Coolant Yes  
Jaw width (mm)  
Jaw height (mm)  
Opening (mm)  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping Yes  
Cross motion table No

### Supplied with:

- Tap-holder chuck M3 to M16
- Self-clamping chuck 16 mm
- Chuck shank