



Photo et textes non contractuels

SPC 40 TC DL

(Ref. 20601138)

Drilling metals, plastic materials and wood, with coolant
Usage très intensif

Guarantee:  

Product Information:

Cross move table, Slow down motion
Steel cast iron frame, head and stand
Steel column
Machined aluminium pulleys
Transmission through V belts with rapid adjustment of tension
Spindle fitted on bearings
Adjustable spindle rack motion through return spring
2-gear motor
24V very low voltage controls :

- ON/OFF
- Switching on lamp
- Emergency Stop through mushroom stop button
- 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- Rack-driven table, graisseur de la vis sans fin
- Hot weather adaptation on request
- Can be modified to 230V three-phase on request
- Machined aluminium pulleys

Technical characteristics:

Height (cm) : 185.00
Width (cm) : 47.50
Length (cm) : 90.00
Net weight (Kg) : 570.00
Power(kW)
Power (V) 3-phase 400V
Spindle speed (rpm)
Max. drilling capacity (mm)
Milling capacity (mm)
Morse taper MT4
Column dia (mm)
Spindle stroke (mm)
Number of gears
d: spindle/column distance (mm)
e: spindle/base distance (mm) 1 150
f: spindle/table distance (mm)
Table dimension (mm)
Distance between table grooves (mm)
Lighting Yes
Servo screen Yes
Reversible vice table No
Coolant Yes
Transversal / longitudinal stroke (mm)
Automatic down motion (mm/tr) No
Slow down motion Yes
Semi automatic tapping No
Cross motion table Yes

Supplied with Self-clamping chuck and Chuck shank