



134 FR

(Ref. 20113035)

Dry grinding and polishing of ferrous metals
Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- "Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Electrical brake powered by an emergency Stop, stop in less than 5 seconds
- Control box complying with high school and administration requirements
- 24V very low voltage controls :
 - Start/Stop
 - Switching on lamp
 - Emergency Stop
 - 3-point locking circuit breaker
 - Lack of voltage-coil safety device
 - Polycarbonate protective shield
 - Motor internal automatic heat protection
 - Pressed metal sheet carters fitted with a nozzle to collect dust
 - Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
 - Hot weather adaptation on request

Technical characteristics:

- Height (cm) : 55.00
- Width (cm) : 33.00
- Length (cm) : 60.00
- Net weight (Kg) : 29.00
- Power(kW) 0.75
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm) 2 800
- Wheel-1 dimension (mm) 200 x 25 x 20
- Brush dimensions (mm) 200 x 25 x 20
- Wheel-1 grain A 60 M
- Brush wire nature Brass-coated steel
- Diameter (mm)