

tank



Photo et textes non contractuels

## Product Information:

"Fitted standard with a class L filter  
Anti-crushing shielded hose  
4-wheel stand for optimised motion  
Dual turbine suction

By-

pass cooling motor (air is sucked up by a third turbine on top of the motor, only for cooling down). Designed for heavy-duty jobs

Vinyl power cable H05 VV-F length 7 m

Separate switch per motor

### Standard accessories:

- plastic tubes
- liquid nozzle
- suceur à poussières
- round brush
- flat nozzle
- hose, length 2,7 m Ø 40 mm

## MC 55 i

(Ref. 20403006)

Water and dust  
suction

**Usage régulier**

Norm: EN 60335-2-69

Guarantee:  

## Technical characteristics:

Height (cm) : 92.50  
Width (cm) : 52.00  
Length (cm) : 52.00  
Net weight (Kg) : 23.00  
Repairability index 8,8/10  
Power (W) 2 x 1000  
Power (V) 1-phase 230V  
Tank stainless steel  
Tank capacity (l) 50  
Depression (Kpa) 22.54  
Flow (l/min) 7 080  
Sound level (dBA) 84  
Atex Zone 22 No  
Accessory diameter (mm) 40  
Unclogging No  
Class-M approved No  
Vacuum cleaner filter Class L  
Synchro socket No  
Cable length (m) 7  
Tank capacity (L) 78