



## D32 - 52 - 67 - 112 - 132

(Ref. 11101515)

Dry drilling of hollow building materials, breeze blocks, bricks, aerated concrete

**Usage intensif**

Photo et textes non contractuels

### Product Information:

Laser-welded segment ring  
Designed for dry core-drilling on portable drilling machine  
Using only the drill to hammer drill a center hole  
No-hammer core-drilling using the ring + center drill  
Assembly with hexagonal rod or SDS PLUS  
Building construction materials: non-reinforced concrete, brick, cellular concrete  
Splines segments to better discharge dust  
Convenient core-rilling and finishing speed in building construction materials

### Technical characteristics:

Height (cm) : 58.50  
Width (cm) : 17.00  
Length (cm) : 31.00  
Net weight (Kg) : 8.61  
For machine Drilling Portable machine  
Diameter (mm) 32 - 52 - 67 - 112 - 132  
Ring length (mm) 15 to 24  
Useful length (mm) 150  
Fitting model R 1/2  
Ring height (mm) 10  
Ring thickness (mm) 3.8  
Number of rings 3 to 9

### Supplied with:

1 center carbide drill Ø 13 x 200 mm  
1 adapter R 1/2 / hexagonal length 88 mm  
1 adapter R 1/2 / SDS PLUS length 115 mm  
1 adapter R 1/2 / SDS MAX length 180 mm  
1 length length 250 mm  
1 blocking rod  
1 Taper drift