

## PRODUCT SHEET | Update File: 12/22/2024 BANDSAWS | Separate down-move band saw



**SR 211 DAV** 

(Ref. 20114130)

Dry steel, stainless steel and aluminium sawing with coolant with coolant

Usage régulier



Photo et textes non contractuels

## **Product Information:**

Steel cast iron arch Band guides fitted with bearings ensuring an excellent wear-resistance of band saw blade Adjustable front mobile band guide Gravity-feed separate down move through oil cylinder 2-point lubrication system through electropump Band-tension microswitch and pressure gauge Fast-tightening vice mounted on clearance catch-up slide Electronic speed variator Front control panel 24V very low voltage controls Emergency Stop through mushroom stay put button Band cover fitted with a positive microswitch Motor protection through thermal circuit breaker Coaxial reducer motor

## Comes with:

- base - band saw blade

- 500 mm adjustable cut stop

## **Technical characteristics:**

Height (cm) : 160.00 Width (cm) : 146.00 Length (cm) : 100.00 Net weight (Kg) : 155.00 Power(kW) 1.5 Power (V) 1-phase 230V Speed (m/min) 20 : 90 Round cutting capacity (mm) at 90 170 Squre cutting capacity (mm) at 90° 150 Rectangle cutting capacity (mm) at 90° 190 x 150 Left round cutting capacity (mm) at  $45^{\circ}$  125 Left square cutting capacity (mm) at 45° 95 Left rectangle cutting capacity (mm) at 45° 120 x 95 Vice opening (mm) 200 Working height (mm) 880 Tape (mm) 2080 x 20 x 0.9