



STAR 20 PE

(Ref. 20501018)

Dry drilling of metals, plastic materials and wood
Usage d'appoint

Guarantee:  

Photo et textes non contractuels

Product Information:

- Steel cast iron column
- V-belt transmission
- Spindle fitted on bearings
- ON/OFF switch fitted with a lack of voltage coil
- Emergency Stop through mushroom stay put button
- Safety-grip microswitch around belt cover
- Protective shield of servo chuck
- Tilting table up to 45 °
- Rack-driven table

Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift
- Screw vice and set of clamps

Technical characteristics:

- Height (cm) : 105.00
- Width (cm) : 34.00
- Length (cm) : 59.00
- Net weight (Kg) : 46.40
- Power(kW) 0.6
- Power (V) 1-phase 230V
- Spindle speed (rpm) 180 - 2740
- Max. drilling capacity (mm) 20
- Morse taper MT2
- Column dia (mm) 72
- Spindle stroke (mm) 80
- Number of gears 12
- d: spindle/column distance (mm) 170
- e: spindle/base distance (mm) 710
- f: spindle/table distance (mm) 505
- Table dimension (mm) 250 x 250
- Lighting No
- Servo screen Yes
- Reversible vice table No
- Coolant No
- Automatic down motion (mm/tr) No
- Slow down motion No
- Semi automatic tapping No
- Cross motion table No