



## SPC 40 TE VEL DA DL

(Ref. 20601137)

Drilling metals, plastic materials and wood, with coolant  
**Usage très intensif**

Guarantee:  **3** 

Photo et textes non contractuels

### Product Information:

- Slow down motion, automatic down motion (3 feed rates)
- Electronic speed variator
- Steel cast iron frame, head and stand
- Steel column
- Machined aluminium pulleys
- Transmission through V belts with rapid adjustment of tension
- Spindle fitted on bearings
- Adjustable spindle mack motion through return spring
- 24V very low voltage controls :
  - ON/OFF
  - Switching on lamp
  - Emergency Stop through mushroom stay put button
  - 3-point locking circuit breaker
- Detachable servo protective shield
- 24V lighting
- Electrical protection IP54
- Noise level 50 dB
- 3-position reversible vice table (with vernier), V jaws to drill tubes
- Vice fitted on guideways to center the part to drill
- Rack-driven table, graisseur de la vis sans fin

### Technical characteristics:

- Height (cm) : 185.00
- Width (cm) : 47.50
- Length (cm) : 90.00
- Net weight (Kg) : 400.00
- Power(kW) 2.2
- Power (V) 3-phase 400V
- Spindle speed (rpm) 80 - 2030
- Max. drilling capacity (mm) 40
- Morse taper MT4
- Column dia (mm) 120
- Spindle stroke (mm) 150
- Number of gears 14
- d: spindle/column distance (mm) 300
- e: spindle/base distance (mm) 1 150
- f: spindle/table distance (mm) 50-610
- Table dimension (mm) 420 x 420
- Distance between table grooves (mm) 150
- Lighting Yes
- Servo screen Yes
- Reversible vice table Yes
- Jaw Width (mm) 150

Hot weather adaptation on request  
Can be modified to 230V three-phase on request  
Machined aluminium pulleys

Jaw height (mm) 40  
Opening (mm) 150  
Automatic down motion (mm/tr) 0.06 - 0.12 - 0.25  
Slow down motion Yes  
Semi automatic tapping No  
Cross motion table No

**Supplied with Self-clamping chuck and Chuck shank**