

PRODUCT SHEET | Update File: 10/22/2025

BANDSAWS | Semi automatic band saw



Photo et textes non contractuels

SR 285 DG SAV

(Ref. 20114128)

Dry steel, stainless steel and aluminium sawing with coolant with

Usage intensif

Guarantee:

Product Information:

Fully-hydraulic semi automatic cycle of band, arch and arch

Electronic speed variator

Semi automatic down move of the arch

Very highly rigid steel cast iron arch

Band guides fitted with bearings and carbide tips ensuring a good wear re sistance to band

Adjustable front mobile band guide

2-point lubrication system through electropump

Vice support tilting with the arch

Hydraulic vice

24V very low voltage controls

Emergency Stop through mushroom stay put button

Band cover fitted with a microswitch

Motor protection through thermal circuit breaker

Electrical protection IP54

Coaxial reducer motor

Supplied with:

- base
- band saw
- adjustable cut stop

Technical characteristics:

Height (cm): 105.40 Width (cm): 75.00 Length (cm): 167.60 Net weight (Kg): 310.00 Power(kW) 1,1

Power (V) 3-phase 400V Speed (m/min) 20:85

Round cutting capacity (mm) at 90 240 Squre cutting capacity (mm) at 90° 240 Rectangle cutting capacity (mm) at 90° 200 x 285

Left round cutting capacity (mm) at 45° 200 Left square cutting capacity (mm) at 45° 180 Left rectangle cutting capacity (mm) at 45° 140 x 180

Left round cutting capacity (mm) at 60° 120 Left square cutting capacity (mm) at 60° 95 Left rectangle cutting capacity (mm) at 60° 95 x 110

Vice opening (mm) 375 Working height (mm) 915 Tape (mm) 2685 x 27 x 0.9

Right rectangle cutting capacity (mm) at 45° 90 x 150 Right round cutting capacity (mm) at 45° 150

Left square cutting capacity (mm) at 45° 140