

PRODUCT SHEET | Update File: 11/2/2025

BANDSAWS | Separate down-move band saw



SR 211 DAV

(Ref. 20114130)

Dry steel, stainless steel and aluminium sawing with coolant with

Usage régulier

Guarantee: 🕃 €



Photo et textes non contractuels

Product Information:

Steel cast iron arch

Band guides fitted with bearings ensuring an excellent wear-resistance of band saw blade

Adjustable front mobile band guide

Gravity-feed separate down move through oil cylinder

2-point lubrication system through electropump

. Band-tension microswitch and pressure gauge

Fast-tightening vice mounted on clearance catch-up slide

Electronic speed variator

Front control panel

24V very low voltage controls

Emergency Stop through mushroom stay put button

Band cover fitted with a positive microswitch

Motor protection through thermal circuit breaker

Coaxial reducer motor

Technical characteristics:

Height (cm): 160.00

Width (cm): 146.00 Length (cm): 100.00

Net weight (Kg): 155.00

Power(kW) 1.5

Power (V) 1-phase 230V

Speed (m/min) 20:90

Round cutting capacity (mm) at 90 170 Squre cutting capacity (mm) at 90° 150

Rectangle cutting capacity (mm) at 90° 190 x 150

Left round cutting capacity (mm) at 45° 125 $\,$

Left square cutting capacity (mm) at 45° 95

Left rectangle cutting capacity (mm) at 45° 120 x 95

Vice opening (mm) 200

Working height (mm) 880 Tape (mm) 2080 x 20 x 0.9

Comes with:

- base
- band saw blade
- 500 mm adjustable cut stop