

## PRODUCT SHEET | Update File: 10/22/2025

BANDSAWS | Separate down-move band saw



Photo et textes non contractuels

## **EXPERT 250 SR DGDAV**

(Ref. 20114137)

Dry steel, stainless steel and aluminium sawing with coolant with

Usage régulier

Guarantee: 3



## **Product Information:**

Cuts left and right

Aircast fram

Saw blade guides equipped with bearings and carbide pads to ensure exc

ellent resistance to saw blade wear

Adjustable anterior tape guide

Autonomous descent by gravity controlled by hydraulic cylinder

2-point electro-pump lubrication device

Safety micro-switch and tension gauge saw blade

Fast-tightening set mounted on game catch-up slide

Varaible speed saw blade

Control desk in front

Very low voltage controls 24 V

Stopping punch to hook

Carter saw equipped with a positive micro-reuptor

Motor protection by heat breaker

Motor with coaxial gearbox

Supplied with base, saw blade and 500 mm adjustable cut stop

## **Technical characteristics:**

Height (cm): 180.00 Width (cm): 100.00 Length (cm): 185.00

Net weight (Kg): 306.00

Power(kW) 1.1

Power (V) 3-phase 400V Speed (m/min) 20:85

Round cutting capacity (mm) at 90 225 Squre cutting capacity (mm) at 90° 225

Rectangle cutting capacity (mm) at 90° 250 x 150 Left round cutting capacity (mm) at 45° 150  $\,$ Left square cutting capacity (mm) at 45° 150

Left rectangle cutting capacity (mm) at 45° 130 x 190

Left round cutting capacity (mm) at 60° 90 Left square cutting capacity (mm) at 60° 90

Left rectangle cutting capacity (mm) at 60° 95 x 90

Vice opening (mm) 250 Working height (mm) 930 Tape (mm) 2470 x 27 x 0.9

Right rectangle cutting capacity (mm) at 45° 45 x 160

Right round cutting capacity (mm) at  $45^{\circ}$  140 Left square cutting capacity (mm) at 45° 115