



## ULTRA 200 TMLT

(Ref. 20113138)

Dry tangential and side grinding of hardened and hard steel  
**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Control box complying with high school and administration requirements
- 4-point locking Start/Stop switch
- Lack of voltage-coil safety device
- Emergency Stop with mushroom stay put button
- Polycarbonate protective shield
- Motor internal automatic heat protection
- Pressed metal sheet carters fitted with a nozzle to collect dust
- Table lapidaire inclinable avec rapporteur d'angle
- Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
- Hot weather adaptation on request
- 3-phase 230V version of the bench grinder on request

### Technical characteristics:

- Height (cm) : 108.00
- Width (cm) : 47.00
- Length (cm) : 55.00
- Net weight (Kg) : 65.00
- Power(kW)
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm)
- Wheel-1 dimension (mm)
- Wheel-2 dimension (mm)
- Wheel-1 grain
- Wheel-2 grain
- Diameter (mm)

### Supplied with:

- Grinding Wheel AA 60 M
- Grinding Wheel A 60 M
- B18 Base