



Photo et textes non contractuels

PRO EDGE 45

(Ref. 20116399)

Usage intensif

Guarantee:  2 

Product Information:

Eliminates the need for angle rods and allows 45° cuts to be made in corners with epoxy resin joints.

The PRO EDGE cutting jig makes 45° cuts quick, easy and highly precise. The tool has a large sliding surface for maximum control of the cut during operation.

The unique M14 spindle locking unit allows you to use any manufacturer's 115-125 mm angle grinder.

A specific ULTRA CERAM 45° 30 bore diamond disc must be used.

The mitre carriage is infinitely adjustable for precise finishing of mitre cuts

3 adjustment functions:

- Adjustment of edge thickness and parallelism of the disc in relation to the tile
- Lower fence adjustment to suit tile thickness.
- Adjustment of the suction housing to suit the thickness of the tile.

The maximum thickness of the material to be processed is 20 mm.

An anti-vibration ring can be fitted between the grinder and the disc to further improve the quality of the cut.

Built-in vacuum function. With the help of a Hoover, you can effectively capture dust thanks to its housing and suction nozzle while cutting, keeping your working environment clean. This not only increases your comfort, but also your safety.

Places have been provided for the installation of water supply hoses.

In the inverted position, the system can be attached to a fixed workstation (e.g. a workbench or tiling table) for processing small tiles.

Supplied with :

- ULTRA CERAM 45° diamond blade with 30° bore
- Multifunctional key
- 8mm Allen key
- Rubber tip 45° angle
- Anti-vibration ring
- Clamp and self-gripping strap (angle grinder can be fixed with a single element)

Technical characteristics:

Height (cm) : 20.00

Width (cm) : 24.00

Length (cm) : 50.00

Net weight (Kg) : 4.49

Disk diameter (mm)

Disk bore (mm)

Left height cutting capacity (mm) 45°

Tile thickness (mm)