



## EXPERT 30 PCTE

(Ref. 20502106)

Dry drilling of metals, plastic materials and wood (optional lubrication)

**Usage régulier**

Guarantee:  

Photo et textes non contractuels

### Product Information:

Steel cast iron column  
Transmission through steel dented belt and wheels  
Spindle fitted on bearings  
ON/OFF switch fitted with a lack of voltage coil  
Emergency Stop through mushroom stay put button  
Protective shield of servo chuck  
Reversible tilting vice table up to 45°, with coolant collector  
Rack-driven table  
Digital readout of the drilling depth  
Digital display of the spindle speed  
Drilling-position laser  
LED lighting  
Pulley cover fitted with a grip-safety microswitch  
Vice on guideways, 200-mm jaws, 165-mm opening

### Supplied with:

- Self-clamping chuck 16 mm
- Chuck shank
- Taper drift

### Technical characteristics:

Height (cm) : 173.00  
Width (cm) : 41.00  
Length (cm) : 76.00  
Net weight (Kg) : 130.00  
Power(kW)  
Power (V) 3-phase 400V  
Spindle speed (rpm)  
Max. drilling capacity (mm)  
Morse taper MT3  
Column dia (mm)  
Spindle stroke (mm)  
Number of gears  
d: spindle/column distance (mm)  
e: spindle/base distance (mm) 1 215  
f: spindle/table distance (mm)  
Table dimension (mm)  
Distance between table grooves (mm)  
Lighting Yes  
Servo screen Yes  
Reversible vice table Yes  
Coolant No  
Jaw width (mm)  
Jaw height (mm)  
Opening (mm)  
Automatic down motion (mm/tr) No  
Slow down motion No  
Semi automatic tapping No  
Cross motion table No