



Photo et textes non contractuels

343 S

(Ref. 20105051)

Sanding of metals, wood,
plastics

Usage très intensif

Guarantee:  

Product Information:

Self-adhesive abrasive disk Ø 350 mm
Tilting table on stone-polisher side from 0° to 45°
Transmission through anti-slipping rubber roller
Graphite-coated canvas ensuring a good running of the band
Lack of tension-coil switch
Thermal circuit breaker
2-gear motor
Emergency Stop through mushroom stay put button
24V very low voltage control
Reinforced metal sheet protective cover fitted with dust collection
nozzle Ø 100 mm
R0° to 90° orientable band cover for horizontal or vertical job, and
band end job
Hot weather adaptation on request
Can be modified to 230V three-phase on request
Supplied fitted on stand
Optional suction system (20105053)

Technical characteristics:

Height (cm) : 122.00
Width (cm) : 85.00
Length (cm) : 72.00
Net weight (Kg) : 100.00
Power(kW) 1.27 / 1.7
Power (V) 3-phase 400V
Rotation speed (rpm) 1400 / 2800
Endless band dimension (mm) 1500 x 120
Working surface table (mm) 445 x 120
Band speed (m/s) 15 / 30
Integrated dust suction optional

Supplied with:

a brown corundum GR60 endless band
a self-adhesive brown corundum GR60 abrasive disk dia 350mm