



116

(Ref. 20113021)

Dry tangential and side grinding of hardened and hard steel

Usage très intensif

Guarantee:  

Photo et textes non contractuels

Product Information:

- Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Control box complying with high school and administration requirements
- 4-point locking Start/Stop switch
- Lack of voltage-coil safety device
- Emergency Stop with mushroom stay put button
- Polycarbonate protective shield
- Motor internal automatic heat protection
- Pressed metal sheet carters fitted with a nozzle to collect dust
- Table lapidaire inclinable avec rapporteur d'angle
- Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
- Hot weather adaptation on request
- 3-phase 230V version of the bench grinder on request

Technical characteristics:

- Height (cm) : 36.50
- Width (cm) : 35.00
- Length (cm) : 62.00
- Net weight (Kg) : 65.00
- Power(kW) 1.1
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm) 2 800
- Wheel-1 dimension (mm) 200 x 40 x 20
- Wheel-2 dimension (mm) 200 x 25 x 20
- Wheel-1 grain AA 60 M
- Wheel-2 grain A 60 M
- Diameter (mm)

Supplied with stand B18