



## 134 FR

(Ref. 20113035)

Dry grinding and polishing of ferrous metals

**Usage très intensif**

Guarantee:  

Photo et textes non contractuels

### Product Information:

- "Cast aluminium body
- Fitted with self-lubricated oiltight bearings
- Electrical brake powered by an emergency Stop, stop in less than 5 seconds
- Control box complying with high school and administration requirements
- 24V very low voltage controls :
  - Start/Stop
  - Switching on lamp
  - Emergency Stop
- 3-point locking circuit breaker
- Lack of voltage-coil safety device
- Polycarbonate protective shield
- Motor internal automatic heat protection
- Pressed metal sheet carters fitted with a nozzle to collect dust
- Adjustable anti-spark shield and tool-holders 2 mm away from the wheel
- Hot weather adaptation on request

### Technical characteristics:

- Height (cm) : 55.00
- Width (cm) : 33.00
- Length (cm) : 60.00
- Net weight (Kg) : 29.00
- Power(kW) 0.75
- Power (V) 3-phase 400V
- Rotation speed 1 (rpm) 2 800
- Wheel-1 dimension (mm) 200 x 25 x 20
- Brush dimensions (mm) 200 x 25 x 20
- Wheel-1 grain A 60 M
- Brush wire nature Brass-coated steel
- Diameter (mm)