



Photo et textes non contractuels

TS 250

(Ref. 20114087)

Cutting-off of metal profiles with coolant

Usage régulier

Guarantee:  

Product Information:

- "45° tilting head to the left and the right
- Rapid clamping vice.
- Burr-free double vice
- Mobile jaw to perform right 45° cut
- Protective cover of detachable saw mill
- Lubrication system of saw mill using a pump
- Drive through an oil-bath reducer
- Steel cast iron frame
- Control arm fitted with a trigger switch
- Very low voltage controls 24 V
- Emergency Stop through a mushroom stay put button
- Gear switch
- Electrical insulation IP 54

Technical characteristics:

- Height (cm) : 157.30
- Width (cm) : 96.00
- Length (cm) : 93.50
- Net weight (Kg) : 130.00
- Power(kW) 0.75 / 0.9
- Power (V) 3-phase 400V
- Rotation speed (rpm) 45 / 90
- Round cutting capacity (mm) at 90° 75
- Square cutting capacity (mm) at 90° 65
- Rectangle cutting capacity (mm) at 90° 90 x 50
- Left round cutting capacity (mm) at 45° 65
- Left square cutting capacity (mm) at 45° 55
- Left rectangle cutting capacity (mm) at 45° 60 x 50
- Vice opening (mm) 100
- Working height (mm) 955
- Dimension of the blade 250 x 2 x 32
- Right rectangle cutting capacity (mm) at 45° 60 x 50
- Right round cutting capacity (mm) at 45° 65
- Left square cutting capacity (mm) at 45° 55
- Abrasive disc dimension (mm) 250 x 2 x 32