



## SR 264 DG DAV

(Ref. 20114121)

Usage intensif

Guarantee:  

Photo et textes non contractuels

### Product Information:

- Left and right cutting
- Autonomous down move of the arch
- Electronic variable speed
- Very highly rigid steel cast iron arch
- Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
- Adjustable front mobile band guide
- 2-point lubrication system through electropump
- Vice support tilting with the arch
- Hydraulic vice
- 24V very low voltage controls
- Emergency Stop through mushroom stay put button
- Band cover fitted with a microswitch
- Motor protection through thermal circuit breaker
- Electrical protection IP54
- Coaxial reducer motor

### Supplie with:

- base
- band saw
- adjustable cut stop

### Technical characteristics:

- Height (cm) : 140.00
- Width (cm) : 66.00
- Length (cm) : 140.00
- Net weight (Kg) : 341.00
- Power(kW) 1,4
- Power (V) 3-phases 400V
- Speed (m/min) 15 : 90
- Round cutting capacity (mm) at 90° 235
- Squre cutting capacity (mm) at 90° 230
- Rectangle cutting capacity (mm) at 90° 280 x 180
- Left round cutting capacity (mm) at 45° 185
- Left square cutting capacity (mm) at 45° 160
- Left rectangle cutting capacity (mm) at 45° 185 x 100
- Left round cutting capacity (mm) at 60° 115
- Left square cutting capacity (mm) at 60° 80
- Left rectangle cutting capacity (mm) at 60° 115 x 80
- Vice opening (mm) 300
- Working height (mm) 900
- Tape (mm) 2710 x 27 x 0.9
- Right rectangle cutting capacity (mm) at 45° 185 x 80
- Right round cutting capacity (mm) at 45° 165
- Left square cutting capacity (mm) at 45° 145