



Photo et textes non contractuels

SR 320 DG DA

(Ref. 20114126)

Usage intensif

Guarantee:  

Product Information:

Left and right cutting
Autonomous down move of the arch
Very highly rigid steel cast iron arch
Band guides fitted with bearings and carbide tips ensuring a good wear resistance to band
Adjustable front mobile band guide
2-point lubrication system through electropump
Vice support tilting with the arch
Hydraulic vice
24V very low voltage controls
Emergency Stop through mushroom stay put button
Band cover fitted with a microswitch
Motor protection through thermal circuit breaker
Electrical protection IP54
Coaxial reducer motor

Supplie with:

- base
- band saw
- adjustable cut stop

Technical characteristics:

Height (cm) : 110.00
Width (cm) : 73.00
Length (cm) : 195.00
Net weight (Kg) : 420.00
Power(kW) 2,2
Power (V) 3-phase 400V
Speed (m/min) 35 / 70
Round cutting capacity (mm) at 90° 270
Square cutting capacity (mm) at 90° 260
Rectangle cutting capacity (mm) at 90° 260 x 320
Left round cutting capacity (mm) at 45° 230
Left square cutting capacity (mm) at 45° 220
Left rectangle cutting capacity (mm) at 45° 220 x 220
Left round cutting capacity (mm) at 60° 140
Left square cutting capacity (mm) at 60° 140
Left rectangle cutting capacity (mm) at 60° 140 x 140
Vice opening (mm) 270
Working height (mm) 980
Tape (mm) 2925 x 27 x 0.9
Right rectangle cutting capacity (mm) at 45°
Right round cutting capacity (mm) at 45°
Left square cutting capacity (mm) at 45°